LUMUX

DATE:
PROJECT:
FIRM:
CATALOG NO.:
COMMENTS:

FLOOD LIGHTS

FL350

The Lumux FL350 is a low-wattage, small footprint flood light used for accent lighting and spot lighting of facades. Constructed from grade 316 stainless steel, the FL350 offers high intensity performance in a compact body and features a minimal, modern design. This fixture is adjustable and could be angled up to 90° to achieve the desired direction of light. This unit is designed for long lasting indoor and outdoor applications.



Housing: Heavy-duty construction of one-piece, corrosion resistant, grade 316 stainless-steel. Enclosed lens. Utilizes vandal resistant, stainless-steel screws.

Lens: 1/8" thick shatter proof clear glass diffuser, anodized aluminum reflector

Mounting: Surface mounted

Installation: Installs into a standard j-box

Finish: Zinc polyester powder coat finish in black, white, silver,

bronze, or any custom RAL color.

Driver: Constant current and universal input voltage 120/277V,

starting temperature rated at -20°F.

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations

Wattage: 3W

Color Temperature: 2700K / 3000K / 3500K / 4000K

Delivered Lumens: 2700K 3000K 3500K 4000K

90Lm 100Lm 110Lm 120Lm

CRI: 90

Warranty: 5 year limited warranty
















Dimensions:





DATE:	
PROJECT:	
FIRM:	
CATALOG NO.:	
COMMENTS:	

FLOOD LIGHTS

FL350

Ordering Guide:

Catalog No.	LED Color	Color Temp ¹	Voltage	Finish
FL350	White	2700K 3000K	120/277	Stainless Steel Black
		3500K 3500K 4000K		White
		4000K		Silver Bronze Custom RAL ²

¹Consult factory for additional options

²Consult factory for additional pricing

Cata	100	N	<u>ا</u>
Cata	ıоч	11	υ.