LUMUX

WALL SCONCES
L309

The Lumux L series combines architectural design and quality with high performance, and features a range of vandal resistant, wall and ceiling mounted luminaries with a variety of grill and visor options. Designed for accent lighting of walls and facades, the Lumux L series is constructed from the highest quality components and is built for optimal performance in any environment while offering elegant and attractive form factors.

MADE IN USA · **ETL LISTED US** · **IP 65** · **Quick Ship**

5 YEAR WARRANTY · **Wet** · **MARINE GRADE** · **TURTLE FRIENDLY**

Housing: Heavy-duty construction of one-piece, corrosion resistant, low-copper (<1% copper) die-cast aluminum. Enclosed lens secured with vandal resistant, stainless-steel screws.

Lens: One-piece, 1/8" thick shatter proof frosted glass

Mounting: Surface mounted, wall or ceiling

Installation: Mounting bracket provided that fits any standard 3.0" or 4.0" J-Box

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Driver: Constant current and universal input voltage 120/277V, starting temperature rated at -20˚F. Dimmable option available (0-10v).

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations

Wattage: 21W

Color Temperature: 2700K / 3000K / 3500K / 4000K

Dimensions:

Delivered Lumens:

2700K	3000K	3500K	4000K
799Lm	866Lm	1010Lm	1154Lm

Please consult factory for higher lumen packages

CRI: 90

Warranty: 5 year limited warranty

10 1/8"

# LUMUX
WALL SCONCES
L309

Ordering Guide:

Catalog No.	LED Color	Color Temp¹	Voltage	Finish	Options²
L309	White	2700K	120/277	Black	☐ Dimmable driver (0-10v)
	Amber	3000K		White	☐ Photocell
		3500K		Silver	☐ 1/2" KO on the sides
		4000K		Bronze	
				Custom RAL²	

¹Consult factory for additional options
²Consult factory for additional pricing
Consult factory for compact fluorescent options

Catalog No.: _____