UD110

DATE:	
PROJECT:	
FIRM:	
CATALOG NO.:	
COMMENTS:	



Housing: Heavy-duty construction of one-piece, corrosion resistant, low-copper (<1% copper) die-cast aluminum. Step baffle frame encloses lens that is secured with vandal resistant, stainless-steel screws.

Lens: 1/8" think shatter proof clear glass diffuser

Mounting: Surface mounted

Installation: Unit's back plate is 5.0"x 71/2" (Width x Length), will cover any standard J-Box.

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color.

Driver: Constant current and universal input voltage 120/277V, starting temperature rated at -20°F. Dimmable option available (0-10v).

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations

Wattage: 18.4W

Color Temperature: 2700K / 3000K / 3500K / 4000K

Delivered Lumens: 2700K	3000K	3500K	4000K	
1370Lm	1530Lm	1780Lm	2042Lm	
CRI: 90				

Warranty: 5 year limited warranty











EMERGENCY BATTER BACKUP AVAILABLE

Dimensions:





UD110

DATE:

PROJECT: FIRM:

CATALOG NO.:

COMMENTS:

Ordering Guide:

Catalog No.	LED Color	Color Temp ¹	Voltage	Finish	Options ²
UD110	White	2700K	120/277		Dimmable driver (0-10v)
	Blue	3000K		Black	Emergency Battery Pack
	Amber	3500K		White	Up only
		4000K		Silver	Down only ³
				Bronze	Up & Down
				Custom RAL ²	

¹Color Temperature applies only to White LED Color

Catalog No.: __

¹Consult factory for additional options ²Consult factory for pricing

³Dark sky compliant and turtle friendly