

DATE:		
PROJECT:		
FIRM:		
ATALOG NO.:		
COMMENTS:		

STEP LIGHTS

SL500SS

The Lumux SL500 series is a family of precision engineered, recessed LED architectural step lights that are designed for durability and performance. Constructed from the highest quality materials and components, this step light is offered in a wide array of form factors and grill options to fit any specification. A diecast aluminum body is seamlessly integrated with its grade 316 stainless-steel faceplate with captive, vandal resistant stainless-steel screws. This step light features a frosty glass diffuser, reducing glare, and is energy efficient for long-lasting indoor and outdoor applications.

Housing: Heavy-duty construction of corrosion resistant, low-copper die cast aluminum. Faceplate secured with vandal resistant, stainless-steel screws.

Lens: 1/8" thick shatter-proof frosty glass diffuser

Mounting: Recessed wall or concrete pour

Installation: Unit is provided with galvanized steel concrete pour box (see diagram for dimensions). Housing provided with ½" conduit opening.

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color. Consult factory for marine grade or anti-microbial finish.

Driver: Constant current and universal input voltage 120/277V, starting temperature rated at -20°F. Dimmable option available (0-10v).

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations

Wattage: 21W

Color Temperature: 2700K / 3000K / 3500K / 4000K

 Delivered Lumens:
 2700K
 3000K
 3500K
 4000K

 564Lm
 627Lm
 732Lm
 836Lm

Warranty: 5 year limited warranty




















Dimensions:





DATE:	
PROJECT:	
FIRM:	
CATALOG NO.:	
COMMENTS:	

STEP LIGHTS

SL500SS

Ordering Guide:

Catalog No.	LED Color	Color Temp ¹	Voltage	Finish	Options ²
SL500SS	White	2700K	120/277	Stainless Steel	☐ Dimmable driver (0-10v)
	Blue	3000K		Black	
	Amber	3500K		White	
		4000K		Silver	
				Bronze	
				Custom RAL ²	

¹ Color Temperature applies only to White LED Color

Catalog No.:_

Concrete Pour Box:



ø 9½"

² Consult factory for additional options