

LUMUX

UP DOWNS

UD200

The Lumux UD200 is a precision engineered architectural LED wall mounted fixture offering direct and indirect light from a single form-factor with no visible hardware in a sleek, symmetrical design. The fixture is constructed with the highest quality of specification grade materials and component parts, while a shielded light source enhances visual comfort.



Housing: Heavy-duty construction of one-piece, corrosion resistant, low-copper (<1% copper) die-cast aluminum. Enclosed lens secured with vandal resistant, stainless-steel screws.

Lens: 1/8" thick shatter proof clear glass diffuser

Mounting: Wall mounted

Installation: Mounting footplate

Finish: Zinc polyester powder coat finish in black, white, silver, bronze, or any custom RAL color.

Driver: Constant current and universal input voltage 120/277V, starting temperature rated at -20°F. Dimmable option available (0-10v).

Gasket: Closed cell silicon foam gasket that seals out moisture, dust, and insects for weather tight operation.

Protection Class: IP65, ETL Listed for wet locations

Wattage: 23W

Color Temperature: 2700K / 3000K / 3500K / 4000K


Delivered Lumens:	2700K	3000K	3500K	4000K
	1040Lm	1140Lm	1240Lm	1424Lm

CRI: 90

Warranty: 5 year limited warranty



Dimensions:



LUMUX

UP DOWNS

UD200

DATE:

PROJECT:

FIRM:

CATALOG NO.:

COMMENTS:

Ordering Guide:

Catalog No.	LED Color	Color Temp ¹	Voltage	Finish	Options ²
UD200	White	2700K	120/277	Black	<input type="checkbox"/> Dimmable driver (0-10v) <input type="checkbox"/> Emergency Battery Pack <input type="checkbox"/> Occupancy Sensor <input type="checkbox"/> Photocell
	Amber	3000K		White	
		3500K		Silver	
		4000K		Bronze	
				Custom RAL ²	

¹Consult factory for additional options

²Consult factory for pricing

Catalog No.: _____